



CLOSED POSITION

OPEN POSITION

NOTES

1. UPPER PANELS TO HAVE 4" STRIPED ENGINEERING GRADE SHEETING
2. LOWER PANELS AVAILABLE FOR STENCILED LOGO
3. FRONT HAS LEFT SLANT, BACK HAS RIGHT SLANT
4. EACH FACE OF BARRICADE IS MOLDED AS ONE PIECE, UPPER AND LOWER PANELS INTEGRAL W/ BOTH LEGS FOR THE MOST RUGGED POSSIBLE CONSTRUCTION
5. ADJACENT BARRICADES INTERLOCK IN CLOSED POSITION FOR COMPACT STORAGE
6. WARNING LIGHT INHERENTLY PROTECTED FROM DAMAGE BY ITS LOCATION BETWEEN THE UPPER PANELS
7. USE LIGHTWEIGHT WARNING LIGHT (NOT INCLUDED)
8. MEETS MUTCD SPECIFICATIONS
9. REFER TO FHWA LETTERS WZ-47 AND WZ-17

REV	REF	DESCRIPTION	BY	DATE
A	----	RELEASED FOR SALES AND PRODUCTION	JIL	5-9-2007

MATERIAL	COLOR AND FINISH	THIRD ANGLE PROJECTION
POLYOLEFIN	WHITE	
TOLERANCES UNLESS OTHERWISE SPECIFIED		
2 PL. DECIMALS ±		N/A
3 PL. DECIMALS ±		N/A
ANGLES ±		N/A

THIS DRAWING IN DESIGN & DETAIL IS THE PROPERTY OF CORTINA TOOL & MOLDING COMPANY. MATERIAL DESCRIBED & INFORMATION CONVEYED MAY NOT BE COPIED, DIVULGED OR USED FOR MANUFACTURING WITHOUT CONSENT. ALL DESIGN AND INVENTION RIGHTS RESERVED.


Cortina A Cortina Company
Safety Products Group
 10706 WEST GRAND AVENUE, FRANKLIN PARK, IL 60131
 CERTIFIED ISO 9002
 www.cortinaco.com

PLASTX TYPE I BARRICADE			
12 X 24 EGR SHEETED TOP PANEL			
4 X 24 PLAIN BOTTOM PANEL			
SCALE AT	SIZE 1 = 20	DRAWING NUMBER	REVISION
DRAFTER	JIL	DATE 5-9-2007	97-01-001 A
CHECKER	JP	DATE 5-9-2007	